

PROTEX® Products herewith declares that PROBoardMAX™ meets the following specifications:

PROBoardMAX™ is a patented extreme-duty water-proof high-density temporary floor and wall surface protection product that is manufactured with 100% certified FSC® Recycled materials, 100% recycled plastics and 100% bio-degradable and recyclable adhesives.

PROBoardMAX™ was specifically designed to have a desirable degree of surface smoothness, high flexural strength and unsurpassed crush and puncture resistance and to be 100% recyclable.

PROBoardMAX™ Specifications

- Materials: FSC® Recycled & 100% Recycled Plastic
- Size: 48" x 96" (4' x 8'), 48" x 72" (4' x 6') and 48" x 48" (4' x 4')
- Thickness: 0.090 (Caliper) - 0.090" – 90 Mil – 90 pt
- Minimum Density: 3.6 – 57.6 lbs. / cu. ft. – 922.7 kg / m3
- Type: Tru-Lay Flat™ Sheets
- Adhesive: 100% bio-degradable and recyclable
Contains 4 gr/m2 PVA, 9.6 gr/m2 China clay and 0.4 gr/m2 boric and fumaric acid
- Internal Bond: Designed to resist delamination
- pH: Contains a pH level above 7.0 to ensure no acidity
- Moisture: 4 – 8%
- Warp / Curl: Not to exceed 1/16" per 6" from flatness
- Color Consistency: Reasonably smooth and uniformly consistent
- Squareness: +/- 0.3%

On behalf of PROTEX® Products;

Brad Wells / Director of Operations

4.2.16
Date

