

PROTEX® Products herewith declares that PROTEX® meets the following specifications:

PROTEX® is a patented vapor permeable high-density standard-duty temporary floor and wall surface protection product that is manufactured with 100% certified FSC® Recycled materials and 100% bio-degradable and recyclable adhesives.

PROTEX® was specifically designed to have a desirable degree of surface smoothness, high flexural strength and excellent crush and puncture resistance and to be 100% recyclable.

### PROTEX® Specifications

Materials:	FSC® Recycled
Size:	48" x 96" (4' x 8'), 48" x 72" (4' x 6') and 48" x 48" (4' x 4')
Thickness:	0.048 (Caliper) - 0.048" – 48 Mil – 48 pt
Minimum Density:	3.4 – 51.2 lbs. / cu. ft. – 820.1 kg / m <sup>3</sup>
Type:	Tru-Lay Flat™ Sheets
Adhesive:	100% bio-degradable and recyclable Contains 4 gr/m <sup>2</sup> PVA, 9.6 gr/m <sup>2</sup> China clay and 0.4 gr/m <sup>2</sup> boric and fumaric acid
Internal Bond:	Designed to resist delamination
pH:	Contains a pH level above 7.0 to ensure no acidity
Moisture:	4 – 8%
Warp / Curl:	Not to exceed 1/16" per 6" from flatness
Color Consistency:	Reasonably smooth and uniformly consistent
Squareness:	+/- 0.3%

On behalf of PROTEX® Products;

\_\_\_\_\_  
Brad Wells / Director of Operations

4.2.16  
Date

